



MANURE SPREADERS

**THE SPREADERS WITH THE MOST FEATURES
AND BEST WARRANTY IN THE INDUSTRY**



Six different spreader models are available. The smaller capacity models are ground wheel driven, the larger models are P.T.O. driven. The Conestoga line of spreaders come standard with a large number of special features.

The best warranty in the industry includes **"10 years"** on the spreader box. **"Lifetime"** on the poly floor and apron chain. Also, these spreaders are covered for the first **"3 years"** for any defects in workmanship and material.

Distributed by:



13477 Benson Ave. • Chino, CA 91710

Ph: 909/548-4848 • Fax: 909/548-4747

www.gearmore.com • sales@gearmore.com



MANURE SPREADERS

GROUND WHEEL DRIVEN

MODEL C-25GD



The C-25GD is designed for 1 - 5 horses. It has a heaped capacity of 25 cu. ft. and requires a minimum of 15 H.P. to tow fully loaded.

MODEL C-50GD



The C-50GD is designed for 5 - 11 horses. It has a heaped capacity of 50 cu. ft. and requires a minimum of 20 H.P. to tow fully loaded.



MANURE SPREADERS

PTO DRIVEN

MODEL C-50PTO



The C-50PTO is PTO driven and designed for 5 - 11 horses. It has a heaped capacity of 50 cu. ft. and requires a minimum of 25 PTO H.P. to tow and spread.

MODEL C-80PTO



The C-80PTO is PTO driven and designed for 11 - 20 horses. It has a heaped capacity of 80 cu. ft. and requires a minimum of 30 PTO H.P. to tow and spread.



MANURE SPREADERS

PTO DRIVEN

MODEL C-125PTO



The C-125PTO is PTO driven and designed for 10 to 25 horses. It has a heaped capacity of 125 cu. ft. and requires a minimum of 35 PTO H.P. power to tow and spread.

MODEL C-175PTO



The C-175PTO is PTO driven and designed for 25+ horses. It has a heaped capacity of 175 cu. ft. and requires a minimum of 40 PTO H.P. power to tow and spread.



FEATURES & BENEFITS

DURABLE, LONG-LIFE CONSTRUCTION

- √ “Cor-ten” copper bearing steel is used to provide atmospheric corrosion resistance four times that of plain carbon steel, for longer service life.
- √ Conestoga boxes are of all-welded construction, chemically washed, painted with epoxy primer, and finished with a highly corrosion resistant, two-part urethane paint.
- √ This combination of all-welded, Cor-ten steel construction and durable finish gives Conestoga spreader boxes an extraordinarily long service life with 10 years warranty.
- √ Additional durability features include hardened sprockets, grade 5 bolts, Oil-impregnated bushings, sealed bearings and heavy-duty roller chain.

ENVIABLE PERFORMANCE

- √ All Conestoga C models come standard with our own design, STAINLESS-STEEL, T-rod apron chain, which provides superior durability and service life.
- √ Beater paddles are a rooster comb design and are bolted on so they can be replaced when wear does occur.
- √ Conestoga spreaders are designed with 12 paddles, more than the competition.
- √ This combination of paddle design and additional paddles improves shredding action and the overall spread pattern.

UNMATCHED CONVENIENCE

- √ Adjustable web drive on all Conestoga C models allows operator to choose four different speeds to spread a light dusting up to a heavy coating.
- √ All Conestoga C Series models come standard with jacks for easy hook up and detachment.

OUTSTANDING WARRANTIES

- √ The durable Conestoga boxes carry a ten year warranty.
- √ The Conestoga poly vinyl floor system has lifetime warranty.
- √ The overall Conestoga warranty is three years, covering defects in material and workmanship.

KEY CONESTOGA STANDARD FEATURES UNAVAILABLE FROM THE COMPETITION ARE:

- "Cor-ten" copper bearing steel is used to provide atmospheric corrosion resistance four times that of plain carbon steel, for longer service life
- Conestoga boxes are all-welded construction, chemically washed, painted with epoxy primer, and finished with a highly corrosion resistant, two-part urethane paint
- All spreader models feature poly vinyl floors
- All Conestoga spreaders come standard with our own design, stainless steel T-rod apron chain, which provides superior durability and service life
- Beater paddles are a rooster comb design and are bolted on so they can be replaced when wear does occur
- Conestoga spreaders are designed with 12 paddles, more than the competition
- This combination of paddle design and additional paddles improves shredding action and the overall spread pattern



Stainless Steel T-rod apron chain and poly floor



Beater paddles are bolt on for easy replacement



Model C-25GD spreader in action

OUTSTANDING FEATURES ALLOWS CONESTOGA TO GIVE THE BEST WARRANTIES IN THE INDUSTRY:

- "10 Years" on the spreader box
- "Lifetime" on the poly floor and apron chain
- "3 Years" for defect in workmanship and material

Note: C-25GD & C-50GD come with upper beater as standard

SPECIFICATIONS:

	C-25GD	C-50GD	C-50 PTO	C-80 PTO	C-125 PTO	C-175 PTO
Capacity, heaped	25 cu. ft.	50 cu. ft.	50 cu. ft.	80 cu. ft.	125 cu. ft.	175 cu. ft.
Number of Horses	1-5	5-11	5-11	11-21	21+	25+
Drive	2-Wheel Ground Drive		540 RPM PTO			
Overall Length	12'	12'	12'	14'	16' 6"	17' 6"
Overall Width	47"	55"	57"	65"	80"	87"
Loading Height	30"	35"	33"	36"	43"	45"
Tire Size	6/12 Traction	5.00/15 Traction	5.90/15 IMPL	9.50/15 IMPL	10/15 SL	14L/16.1 SL
Weight	600 lbs	825 lbs	825 lbs	950 lbs	1,700 lbs	1,900 lbs

Specifications Subject To Change Without Notice