



FLAIL MULCHERS HYDRAULIC DRIVEN

FOR MOUNTING ON COMPACT EXCAVATORS

seppi m.
MULCHING EQUIPMENT SPECIALISTS



These Flail Mulchers are ideal for grasses and brush that are difficult to reach, like edges of roads and riverbanks. These units shred material up to one inch in diameter. The Mulchers are very productive even with the low hydraulic power required. The hood is made of wear resistant steel. The adjustable rear roller is reinforced and the floating mount adapter are standard equipment. These mulchers are strong, yet light weight for better control. Available cutting widths of 33 & 41 inch.



Marketed by:



13477 Benson Ave. • Chino, CA 91710

Ph: 909/548-4848 • Fax: 909/548-4747

www.gearmore.com • sales@gearmore.com



FLAIL MULCHER HYDRAULIC DRIVEN

FEATURES:

- Mounts to compact excavators and other types of hydraulic booms
- For excavators weights of 4,000 to 10,000 pounds
- Mulches grass and brush up to 1 inch
- Variable displacement hydraulic motor with relief valve
- Required hydraulic flow – 5 to 18 gallons per minute
- Hydraulic pressure 2,175 to 3,625 PSI
- Hood is made of high tensile, wear resistance AR400 steel
- Floating adapter mount to follow the contours of the ground
- Adjustable rear roller with reinforced bearings
- Belts for final drive
- Front mounted safety chains
- Rear mounted safety rubber flaps
- Available with Y blades
- Less Hoses
- Requires case drain line

Option: Hydraulic rotation plate 190°

Heavy duty models available to mulch material up to 16 inch diameter

Your Gearmore Dealer:



SPECIFICATIONS:

MODEL #	WORKING WIDTH	OVERALL WIDTH	DEPTH	NUMBER OF BLADES	WT.
H3-85	33"	38"	31"	12	400#
H3-105	41"	46"	31"	18	480#

Specifications Subject To Change Without Notice

13477 Benson Ave. • Chino, CA 91710 • Ph: 909/548-4848 • Fax: 909/548-4747